

Performance Warranty – multitread nosing's with Carbigrip infill

General :

multitread nosing and tread profiles, (when supplied with Carbigrip infilling), are warranted against premature wear for a period of 10 years, subject to the following:

Extent:

The warranty period commences on the date of supply and applies to the multitread product named on the accompanying advice note where it is proven that such product has failed in its performance due to defective materials or poor manufacturing workmanship.

Limitation:

The warranty extends only to the free issue of replacement product(s). No claim will be entertained for the reimbursement of monies

Conditions:

- ◆ The supplied product must be appropriate for the particular application/environment.
- ◆ The substrate to which the product is to be attached must be sound and/or prepared in accordance with our recommendations.
- ◆ The installation must be in accordance with our recommendations.
- ◆ A cleaning and maintenance regime must be adopted in accordance with our recommendations.
- ◆ Quantick Safety Systems Limited reserve the right to make periodic inspection of the installed product during the period of the warranty.
- ◆ Quantick Safety Systems Limited reserve the right to seek the opinion of a qualified third party in the event of any warranty dispute

Exclusions:

The warranty will be nullified with immediate effect if this supplied product:

- ◆ Has been damaged or misused by a third party.
- ◆ Has been damaged by chemical spillage.
- ◆ Has been damaged due to structural movement.
- ◆ Has been damaged by impact to the building.

Defects:

Reports of product failure must be notified in writing to Quantick Safety Systems Ltd within 7 days of first observation. Quantick Safety Systems Ltd must be allowed to inspect the installation and to take photographs and samples if required for assessment.

Consequential Loss:

Quantick Safety Systems Ltd shall not be liable for consequential loss or damage sustained by their client, whether or not a claim for product failure is upheld under the terms of the warranty. This includes but is not exclusive to, damage to their premises, interruption or interference with their business activities and any make good costs.

The information contained on this data sheet is current at the time of printing. Due to continuing development in machinery and materials, we reserve the right to modify the formulation without notice. The above information is given as a guide to the uses of multitread it is the responsibility of the user to ensure the suitability for specific applications. All recommendations statements and technical data contained herein are based on tests we believe to be accurate and reliable, but accuracy and completeness of such tests are not guaranteed and are not to be construed as a warranty, either express or implied. The user shall rely on their own information and tests in determining suitability of the product for the intended use and assumes all risks and liability from their use of the product. Sellers and manufacturers sole responsibility shall be to replace that portion of this manufacture which proves to be defective. Neither seller nor manufacturer shall be liable to the buyer or any third party for any injury, loss or damage directly or indirectly resulting from the use of the product. Recommendations or statements other than contained in a written agreement signed by an officer of the manufacturer shall not be binding upon the manufacturer or seller.